

```

void FFT1( int *A, int n, int *W, int p, int *T )
{
    int i,n2,t;
    if( n==1 ) return;
    n2 = n/2;

    for( i=0; i<n2; i++ ) {
        T[ i ] = A[2*i];
        T[n2+i] = A[2*i+1];
    }

    FFT1( T,    n2, W+n2, p, A );
    FFT1( T+n2, n2, W+n2, p, A+n2 );

    for( i=0; i<n2; i++ ) {
        t = mulmod(W[i],T[n2+i],p);
        A[ i ] = addmod(T[i],t,p);
        A[n2+i] = submod(T[i],t,p);
    }
    return;
}

void FFT2( int *A, int n, int *W, int p, int *T )
{
    int i,n2,t;
    if( n==1 ) return;
    n2 = n/2;

    for( i=0; i<n2; i++ ) {
        T[i] = addmod(A[i],A[n2+i],p);
        t = submod(A[i],A[n2+i],p);
        T[n2+i] = mulmod(t,W[i],p);
    }

    FFT2( T,    n2, W+n2, p, A );
    FFT2( T+n2, n2, W+n2, p, A+n2 );

    for( i=0; i<n2; i++ ) {
        A[ 2*i ] = T[i];
        A[2*i+1] = T[n2+i];
    }
    return;
}

```